

# Product Spec Sheet from Rentex

## 24" Dell P2415Q Ultra HD 4K Monitor

Download Spec Sheet @ [www.rentex.com/spec/4K02400.pdf](http://www.rentex.com/spec/4K02400.pdf)

Rentex Product No. 4K02400



Mfr Part No. P2415Q

The P2415Q 24" Ultra HD 4K Monitor from Dell offers a viewable display of 23.8" and a resolution of 3840 x 2160 that provides over 8 million pixels, which gives you four times more detail than a 24" class Full HD resolution monitor. The high pixel density lets you see finer details on screen, so you can better view and edit higher resolution photos and more. You can connect this monitor to your computer through a variety of ports that include a DisplayPort, mini DisplayPort, and HDMI. Furthermore, this monitor allows you to daisy-chain another monitor via the DisplayPort's in and out ports, and it connects to smartphones and tablets using an optional MHL HDMI cable. In addition to the video ports, the monitor is equipped with four USB 3.0 ports for connecting numerous USB devices. This monitor is built with an IPS panel that provides 178° viewing angles and 1.07 billion colors.

### Features

- In-Plane Switching (IPS) Technology
- DisplayPort Input + DisplayPort Output
- Mini DisplayPort + HDMI (MHL) Inputs
- 3840 x 2160 Resolution
- 2,000,000:1 Contrast Ratio
- Built-In USB 3.0 Hub

### Detailed Specifications

<b>Viewable Size</b>	23.80" / 60.47 cm (diagonal)	<b>Color Support</b>	1.07 billion colors
<b>Aspect Ratio</b>	16:9 widescreen	<b>Pixel Pitch</b>	0.13725 mm (W) x 0.13725 mm (H)
<b>Panel Type/Surface</b>	In-plane switching (IPS)	<b>Backlight Technology</b>	LED edgelight system
<b>Optimal Resolution</b>	3840 x 2160 at 60 Hz	<b>Display Type</b>	Widescreen panel display
<b>Inputs</b>	1 x DisplayPort 1 x Mini DisplayPort 1 x HDMI (MHL) 1 x USB upstream	<b>Display Screen Coating</b>	Anti-glare treatment of the front polarizer (3H)
<b>Outputs</b>	1 x DisplayPort 1 x Speaker-line 4 x USB 3.0 downstream	<b>Flat Panel Mount Interface</b>	VESA (100 mm)
<b>Display Area (H x V)</b>	20.75 x 11.67" / 527.05 x 296.42 mm	<b>Voltage Required</b>	100 to 240 VAC / 50 or 60 Hz $\pm$ 3 Hz / 1.8 A (maximum)
<b>Contrast Ratio</b>	Typical: 1,000 to 1 Dynamic: 2 million to 1	<b>Power Consumption</b>	90 W (maximum) / 45 W (typical)
<b>Brightness</b>	300 cd/m <sup>2</sup> (typical)	<b>Flat Panel Mount Interface</b>	VESA (100 mm)
<b>Response Time</b>	Grey-to-Grey. 8 ms (typical), 6 ms (fast)	<b>Dimensions (HxWxD)</b>	13.23 x 22.31 x 1.85" (without stand)
<b>Viewing Angle</b>	178° vertical / 178° horizontal	<b>Weight</b>	7.36 lb / 3.34 kg
<b>Adjustability</b>	Tilt, pivot, height adjustable, and swivel		