

# DCS-100

## Dual-channel true seamless switcher

HDCP  
COMPLIANT

2  
LAYERS

up to  
WUXGA  
COMPATIBLE



The DCS-100 is a dual-channel switcher designed to provide true seamless switching between different input sources and formats, while maintaining superb scaling quality at an affordable price. It has been designed for straightforward and simple operations, which makes it the ideal seamless switcher for live events, boardrooms, hotel ballrooms, houses of worship, lecture halls, training facilities and more.

**BARCO**

Visibly yours

## Product specifications

## DCS-100

Front panel control	
Display section	<ul style="list-style-type: none"><li>■ Four (4) line, 128x32 VFD Display</li><li>■ Menu navigation via rotary encoder knob, Select/Escape buttons</li></ul>
Inputs section	<p>Ten buttons select the corresponding input source, or the stored LOGO image, to be placed on program after the TAKE button is pressed. There are three button states:</p> <ul style="list-style-type: none"><li>· Off: The source is not currently on program</li><li>· Blinking: The source has been selected and will be placed on program after the TAKE button is pressed</li><li>· Yellow: The source is on program.</li></ul>
Effects section	<ul style="list-style-type: none"><li>■ FRZ: Instantly freezes the current image that is on program.</li><li>■ BLK: Cuts the program to black</li><li>■ KEY: The key source will transition to/from program, after the TAKE button is pressed</li><li>■ TAKE: Transitions the selected source or KEY at the pre-selected rate.</li></ul>
Inputs	
Six analog inputs via HD-15 VGA connectors	<ul style="list-style-type: none"><li>■ Supports YPbPr, RGBHV, S-video and composite</li><li>■ 10-bits/color sampling at maximum 170 MHz</li><li>■ True pixel mapping (1:1) for signal resolutions up to 1600x1200@60 Hz. Sources with higher pixel rates (1920x1080p@60, 1920x1200@60 and 2048x1080p@60) are also supported.</li></ul>
Two digital or analog inputs via DVI-I connectors	<ul style="list-style-type: none"><li>■ 8-bit digital input per DDWG 1.0 with HDCP support.</li><li>■ RGBHV data via analog pins of the DVI-I connector</li><li>■ The digital source will be processed if valid DVI signals are detected. The Analog source can be selected via the front panel menu.</li></ul>
Serial digital input (HD/SD SDI) via BNC connector	<ul style="list-style-type: none"><li>■ SD SDI per SMPTE 259M-C (NTSC/PAL resolution)</li><li>■ HD SDI per SMPTE 292M (HDTV)</li></ul>
Outputs	
Outputs	<ul style="list-style-type: none"><li>■ Program output in digital format on the DVI-I connector and in analog format on the HD-15 connector.</li><li>■ Progressive resolutions at RGBHV</li><li>■ HDCP Encryption support for DVI signals</li></ul>
Connectors	
Ethernet	RJ-45 connector for 10/100Base-T Ethernet communications
Serial RS-232	DB-9 connector for communicating with external serial devices