

Specification Sheet - Version: 1.3 Chroma-Q[™] Color Force[™] 12 RGBA Multi-Purpose LED Fixture Part No: CHCF12NFRGBA

DESCRIPTION

The fixture shall provide a very powerful 2,400 hot lumens output for washing areas up to 8m / 26ft high.

The fixture shall be suitable for a wide range of entertainment lighting disciplines, including uplighting, pipe-end, shin-busting, backlighting and wash applications.

The fixture shall be suitable for floor, wall or truss mounting.

The fixture shall provide RGBA colour mixing. The fixture shall provide a high CRI of 92.

The fixture shall provide a smooth, linear dimming curve.

The fixture shall offer a choice of HSI, Fx HSI, RGB (*Magic AmberTM), RGBA, RGBI (Magic Amber), St RGBI (Magic Amber) and St RGBA control modes. The fixture shall feature a built-in stand-alone mode with real-time triggering.

The fixture shall feature a built-in power supply.

The fixture shall be manufactured from extruded material.

*Magic Amber is the term used for the unit's ability to bring in amber when mixing colours that require it.

FEATURES

- Suitable for a wide range of entertainment lighting disciplines.
- Floor, wall or truss mountable.
- 2,400 hot lumens output easily washes 8m / 26 foot.
- Extremely smooth, uniform wash.
- RGBA colour mixing.
- Radically increased colour palette.
- High CRI of 92.
- Theatrical grade dimming.
- Rugged extruded aluminium body.
- Built-in power supply.
- Hidden fixing and cable management for seamless wall washing and fast deployment.
- Perfect for theatre, TV, concert touring, exhibitions and corporate events.
- Optional 'Cyc' and 'Border' lens media accessories available.
- Optional Barn Door, Top Hat and Half Top Hat accessories available.

OVERALL SPECIFICATIONS

Net dimensions: Width: 335mm / 13.2"

Height: 190mm / 7.5" Depth: 218mm / 8.6"

Net weight: 4kg / 9lb

Shipping dimensions: Width: 432mm / 17"

Height: 343mm / 13.5" Depth: 279mm / 11"

Shipping weight: 6kg / 13lb Power supply: Built-in

Power input rating: 100-240V AC, 50-60 Hz, 160VA

Power factor: 0.997 Power consumption: 120W

Typical power & current: Measurements done with all LEDs at max.

intensity. Measurements made at nominal voltage. Allow for a deviation of +/- 10%.

OVERALL SPECIFICATIONS cont.

Power connectors in/out: PowerCon
Data connectors in/out: XLR 5-pin
Max cable run: NA

Control protocol: ANSI E1.11 USITT DMX 512-A

Cooling system: Forced - 1 fan Operating temperature: 0°C to 40°C

Construction: Anodised aluminium extrusion

Colour: Black LED engines: 2

LEDs per engine: 24 (6 x RGBA)

Total LEDs: 48

Control modes: 7 channels Fx HSI

6 channels HSI Duo

6 channels RGB (Magic Amber) Duo

8 channels RGBA Duo

9 channels St RGBI (Magic Amber) Duo

5 channels St RGBA 3 channels HSI

3 channels RGB (Magic Amber)

4 channels RGBA


4 channels RGBI (Magic Amber)

1 channel Look Select Master Standalone Slave Standalone

Dimming curve: Theatrical Variable effects engine: Yes

Effects parameters: Colour speed, colour range, colour step,

and intensity effects



* measured at centre of beam

Hot lumen output: White 2,400 lumen

CRI: 9

Optics: Specialised close focus lens

Beam angle: 23° (approx.)
With optional Cyc lens: 80 x 30° (approx.)
With optional Border lens: 60° (approx.)

Beam dispertion: Asymmetrical direct illumination CCT: Adjustable 1,000 – 10,000K Colour Gamut: Performance enhanced Lamp life: L70 up to 50,000 hours



Specification Sheet - Version: 1.3 Chroma-Q[™] Color Force[™] 12 RGBA Multi-Purpose LED Fixture Part No: CHCF12NFRGBA


IP rating: Built-in hardware: Approvals: IP20 Quick release lever for tilt adjustment CISPR 22 :2006/EN55022 :2006 & CISPR 24 :1997/EN55024 :1998, ICES-003 :2004 & FCC Part 15 Subpart B: 2007, CSA C22. No. 166-M1983:R2008 UL 1573:2003; UL 8750


ORDERING INFORMATION


CHCF12NFRGBA: Chroma-Q Color Force 12 RGBA body finished in black

ACCESSORIES

CHCFBL12: Chroma-Q Border lens for Color Force 12 CHCFCL12: Chroma-Q Cyc lens for Color Force 12 CHCFECL12: Chroma-Q Egg Crate Louver for Color Force 12 CHCFHTH12: Chroma-Q Half Top Hat for Color Force 12 CHCFBD12: Chroma-Q Barn Door for Color Force 12 CHCFTH12: Chroma-Q Top Hat for Color Force 12







CE

Chroma-Q and all associated product names are recognised trademarks, for more information visit www.chroma-q.com/trademarks. The rights and ownership of all trademarks are recognised. The information contained herein is correct at the time of printing, however as we are constantly refining our product range we reserve the right to change the specification without notice. E&OE.