

# Product Spec Sheet from Rentex

## Barco S3 4K Screen Management System

800.545.2313

Download Spec Sheet @ [www.rentex.com/spec/ENC3100.pdf](http://www.rentex.com/spec/ENC3100.pdf)

Rentex Product No. ENC3100



Mfr Part No. S3-4K

Featuring 12 input channels, 4 PROGRAM outputs, 4 AUX outputs and 2 dedicated Multiviewer outputs, the S3-4K is the E2 image processor's more compact sidekick. Under the hood, however, it boasts the same processing performance, image quality, flexibility and rugged durability. In short: all the tools you need to create a stunning live experience, in a single compact and roadworthy housing.

### Features

- Video inputs** 12 inputs via 3 input cards (same cards as E2 Event Master Processor)
  - Up to 3 x 4K inputs - each input card supports up to 4K@60p
  - 4 x SD/HD/3G SDI (6G ready)
  - 4 x HDMI 1.4a (297 Mpix/sec max)
  - 4 x DisplayPort 1.1 (330 Mpix/sec max)
- Video Outputs** 10 outputs via 3 output cards (same cards as E2 Event Master Processor)
  - Up to 2x 4K outputs - each output card supports up to 4K@60 p
  - 4 x SD/HD/3G SDI (6G ready)
  - 4x HDMI 1.4a (297 Mpix/sec max)
  - 2 x HDMI 1.4a for Multiviewer (297 Mpix/sec max)
- Genlock** Analog reference input/loop on BNC connectors; bi-level and blackburst at SD and tri-level at HD
- Program Output** 4 program outputs configurable as single screens or tiled/blended widescreens
  - Configurable from 4X 2048X1200@60 max to 1 x 4096x2400@60 max
  - Independent edge blending/feathering control for all four sides
- Scaled Aux Outputs** User definable from 4 x 2048x1200@60 to 1 x 4K@60  
Output color correction
- Mixers** Native resolution background mixer per output screen;  
Independent layer transitions or full Preview/Program transition;  
Flexible layer allocation – 4 scalable PIP/key layer mixers assignable to any Program output screens
- Still Stores** Available in background or PIP
- Layer Effects** Borders (hard, soft, halo) and drop shadows;  
Color effects;  
Strobe, H&V flip;  
Luma key;  
PIP moves via Keyframes

- Native 4K input and output supported
  - Easy expansion thanks to interlinking of chassis
  - Compact and modular design
- 
- Multiviewer** Flexible user-definable layouts;  
Monitor all Inputs and Outputs, including Preview and Aux;  
Two outputs;  
Dedicated hardware same as E2 Event Master Processor
  - Expandability** Easily expandable for larger display applications via proprietary links;  
Link units to increase available Inputs and Outputs for larger tiled/blended widescreen applications;  
Expansion via simple linking - up to 4 chassis;  
S3-4K ships with 2 box linking up to 4 chassis link software available Q2 2016
  - HDCP** HDCP compliant
  - Control** Event Master screen management software for PC or MAC;  
Ethernet RJ-45, 1000/100/10 Mbps autosense
  - Serviceability** Field-Serviceable I/O and processing cards (not hot-swappable);  
Hot swappable dual-redundant power supplies
  - Power** Input power: 100-240 VAC 50/60Hz 700W  
Dual-redundant, hot-swappable power supplies; same as E2 Event Master processor
  - Dimensions** Height: 13.26 cm / 5.22 inches 3 rack mount units  
Width: 43.2 cm / 17 inches without chassis handles,  
48.3 cm / 19 inches with chassis handles attached  
Depth: 54 cm / 21.33 inches overall
  - Weight** 24 kg / 53 lbs

**RENTEX**  
Computer & Audio Visual Rentals "Since 1980"

(800) 545.2313  
[www.rentex.com](http://www.rentex.com)

Boston | New York/NJ | Philadelphia | Washington D.C. | Orlando | Las Vegas | Dallas/Ft Worth | Chicago | Anaheim/LA