

DATA SERIES PROJECTOR TH1060P



BRING YOUR AUDIENCE TO THE BIG SCREEN



High-definition performance—
Clear, widescreen images draw in audiences and add impact to video and picture content



Ideal for large rooms—Bright images
and high contrast ratio guarantee color excellence and fine detail



Built for business—Presentation-
friendly IR remote features USB mouse function and laser pointer



Ready for remote control—Supports
Crestron RoomView for management and control via RJ45 connection



Environmentally-friendly design –
Consumes <1 watt of power in standby mode



The Optoma TH1060P, a native 1080p high-definition DLP projector, delivers clear widescreen images to ensure that your audience experiences the full impact of your message. Bright enough for use in large conference rooms and classrooms, the Optoma TH1060P includes a wide range of analog and digital connectivity options for your high-resolution output sources. The Crestron RoomView® user-friendly interface lets you easily monitor, manage and control the Optoma TH1060P remotely via RJ45 connectivity.

CONNECTIVITY (May require optional accessories)



COMPUTERS



SMART
PHONES



TABLETS



BLU-RAY/DVD PLAYERS



SET TOP BOXES



CAMCORDERS



GAME
CONSOLES



DIGITAL
CAMERAS

DATA SERIES PROJECTOR — TH1060P

OPTICAL/TECHNICAL SPECIFICATIONS

Display Technology	Single 0.65" DC2 DMD DLP Technology by Texas Instruments
Native Resolution	HD (1920 x 1080)
Brightness	4500 ANSI lumens
Contrast Ratio	2500:1 (full on/full off)
Displayable Colors	1.07 Billion
Lamp Life and Type*	3000/2000 Hours (STD/bright) 300W P-VIP
Projection Method	Front, rear, ceiling mount, table top
Keystone Correction	±15° Vertical
Uniformity	85%
Aspect Ratio	16:9 Native, 4:3 compatible
Throw Ratio	1.59 to 1.91:1 (distance/width)
Projection Distance	3.28' to 32.8' (1.0 to 10m)
Image Size (Diagonal)	23.6" to 300" (0.6 to 7.62m)
Projection Lens	F=2.5-2.76, f=23.5-28.2mm, 1.2x manual zoom and focus
Offset	115%
Audio	3-watt speaker
Noise Level (STD/Bright)	28dB/30dB
Remote Control	IR remote mouse control
Operating Temperature	41 to 104°F (5 to 40°C), 85% max humidity
Power Supply	AC input 100-240V, 50-60Hz, auto-switching
Power Consumption	380 watts (bright), 320 watts (STD), <1 watt (standby)

COMPATIBILITY SPECIFICATIONS

Computer Compatibility	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA resized, VESA, PC and Macintosh compatible
Video Input Compatibility	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)
Vertical Scan Rate	50 to 85Hz
Horizontal Scan Rate	15, 31 to 90 KHz
User Controls	Complete on-screen menu, adjustments in 23 languages
I/O Connection Ports	Two HDMI, VGA-in, VGA-out, component, S-video, composite video, stereo RCA audio-in, stereo audio-out, RS-232, USB, RJ45 and 12V trigger
Loop Through (Audio, VGA)	Monitor: D-Sub 15 pin VGA output (functional in both normal and standby modes)

PHYSICAL SPECIFICATIONS

Security	Kensington® Lock Port, security bar and keypad lock
Weight	7.8 lbs (3.53kg)
Dimensions	12.8" x 4.29" x 10.19" (326 x 109 x 259 mm)

*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

** 3D content can be viewed with active LCD shutter glasses or RF glasses when projector is used with compatible 3D player. Please visit www.optoma.com for more information.



Warranty

Three-year Optoma Express Replacement Service, One-year on lamp

What Comes in the Box

AC power cord, VGA to VGA cable, remote control, batteries for remote, carrying case, lens cap, multilingual CD-ROM user's manual, quick start card and warranty card

Optional Accessories

HDMI cable, ceiling mount, VGA to component cable, S-video cable, composite video cable, RS-232 cable and Panoview™ Series screens

Lamp: BL-FS300C
Mount: BM-5001U
Remote: BR-5033L
Case: BK-4013

UPC: 796435 41 719 2

www.OptomaUSA.com

Optoma
Projector Expert

Copyright © 2012 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. All other trademarks are the property of their respective owners. All specifications subject to change at any time. The Optoma Express Program is only valid in the U.S.