Product Spec Sheet from Rentex

Panasonic PT-DZ10KU 3-Chip DLP Projector



Mfr Part No. PT-DZ10KU Rentex Product No. 7550

Detailed Specifications

Display System	3-
Native Resolution	W
Supported Resolutions	V
Format	N
Pixels	6,
Brightness	Ν
Uniformity	90
Aspect Ratio	Ν
Contrast Ratio	1(
Dynamic Contrast Ratio	Ν
Scan	H Ve
Inputs	1)
	1) 1)

-Chip 0.96" / 24.38 mm /UXGA - 1920 x 1200 GA - 640 x 480 ITSC 4.43; PAL 60, M, N; ,912,000 lormal Mode: 10600 Lu 0% lative: 16:10 0000:1 lone lorizontal: 15 - 100 kHz ertical: 24 - 120 Hz x BNC Video (Input) x DVI-D Video (Input) x HDMI Audio/Video (I 5x BNC Component Vide 1x 15-pin VGA Video (In 1x BNC Composite Vide 2x 9-pin VGA Control (In 1x 9-pin VGA Control (O 1x M3 Control (Input) 1x M3 Control (Input) 1x Ethernet LAN (Input) The Panasonic PT-DZ10KU 3-Chip DLP Projector features a dual-lamp system that helps make its body compact, while providing a full 10,600 lumens of brightness in dual lamp mode. When in Lamp Relay Mode, the projector eliminates any interruptions if a lamp should fail, and enables 24/7 projection. The projector's Dynamic Iris feature uses a scene-linking aperture mechanism to achieve a contrast ratio of 10,000:1 without lowering its brightness.

The wide adjustment range of the powered horizontal/vertical lens shift function can be easily adjusted with the remote control. The unit can also be rotated 360° vertically, to accommodate various installation conditions. The lens-centered design contributes to easy installation. High brightness, along with a contrast ratio of 10,000:1, helps produce bright, crisp, and sharp images.

Features

- Brightness of 10,600 Lumens in Dual Mode
- 1920 x 1200 Resolution
- 10,000:1 Contrast Ratio

m DLP	Wireless LAN	None
	Features	Picture-in-Picture, Ceiling Mountable, Rear Screen Projection, Projection Tilt Option
N; SECAM	Max Pixel Clock	162 MHz
umens	Optical Axis Shift	Vertical: ±55% Horizontal: ±20%
	Keystone correction range	Vertical: ±40° Horizontal: ±15°
	Projection Size	70 - 600" / 1778.00 - 15240.00 mm
	Installation	Ceiling/floor, front/rear
z	Lamp Type	355 W UHM lamp x 2
	Lens	Optional powered zoom/focus lenses
	Power Consumption	970 W
(Input) deo (Input) nput) eo (Input) Input) Output)	Power Supply	120 V AC, 9.5 A, 60 Hz
	Dimensions (WxHxD)	20.9 x 7.9 x 21.6"
	Weight	52.91 lbs / 24.00 kg



24/7/365 Sales & Technical Support