

Product Spec Sheet from Rentex

32" Elo 3201L Interactive Digital Signage Touchscreen (IDS)



Mfr Part No. 3201L
Rentex Product No. TCH3220

Elo's new 3201L 32-inch interactive digital signage touchscreen delivers a professional-grade large format display in a slim, integrated package. The Elo display is a 32.0" diagonal, Active matrix TFT LCD with LED backlight. It boasts of 16.7 million Colors with a full HD 1920 x 1080 display.

Features

- Aspect ratio 16:9
- True High Definition (HD) 1080p (1920 x 1080)
- Analog VGA, HDCP-capable HDMI 1.3 and DisplayPort 1.1a, Four 5W stereo speakers
- Projected Capacitive multitouch
- 30"W x 18"H x 3.1"D | 29.8 lbs

Detailed Specifications

Display	32.0" diagonal, Active matrix TFT LCD with LED backlight	Input Frequency	Horizontal: 60 - 73 kHz Vertical: 47-63 Hz
Aspect Ratio	16:9	Input Video Format	Analog VGA, HDCP-capable HDMI 1.3 and Display Port video
Useful Screen Area	Horizontal: 27.5" (698 mm) Vertical: 15.5" (393 mm)	Input Video Signal Connector	Female DE-15 for Analog VGA HDMI 1.3 ON Type A DisplayPort 1.1a
Display Technology	Full HD 1920 x 1080 (native) active matrix	Audio Input Signal Range	1 Vrms max. stereo signal
Colors	16.7 million	USB Ports	Type B
Brightness	LCD panel: 350 nits With IntelliTouch Plus: 315 nits With Projected Capacitive: 301 nits	Touch Technology	IntelliTouch Plus
Response Time	8.0 msec	Audio Input Connector	3.5 mm TRS jack
Viewing Angle	Horizontal: $\pm 89^\circ$ or 178° total Vertical: $\pm 89^\circ$ or 178° total	Speakers	4 x 5W stereo speakers
Contrast Ratio	3000:1	Power Connector	IEC 60320 C14
On-Screen Display	Controls: Menu, Up, Down, Select, Power Settings: Brightness, Contrast, Clock, Phase, Auto-Adjust, H-position, V-position, Auto- Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Source Lockouts : OSD, Power	Power Supply	Internal AC
		Input Voltage	110-230 VAC 50/60Hz
		Dimensions (WxHxD)	30" x 18" x 3.1"
		Weight	29.8lbs