Product Spec Sheet from Rentex

Samsung MD65C 65" LED Monitor with Multi-Touch Touchscreen



Mfr Part No. MD65C Rentex Product No. TCHO650M

Detailed Specifications

The Samsung MD65C edge-lit display features 1920 x 1080p full HD resolution with 550-nit brightness and a 5000:1 contrast ratio for sharp, detail-rich images and crisp, easily-legible type. Built-in WiFi delivers seamless Internet connectivity, the integrated WiDi (Wireless Display) technology allows wireless viewing of HD video from enabled PCs, and a built-in TV tuner provides the option of easily displaying broadcast TV. For interactive applications, the monitor's IR touch overlay accepts up to 6 simultaneous touch points.

Features

- 1920 x 1080 Resolution
- 65" 60Hz (Slim Direct-LED Backlight)
- 4000:1 Contrast Ratio
- 59.1"W x 34.7"H x 2.5"D including touch screen
- 109.2 lbs including touchscreen

| Screen Size | 65″ | Features | Built-in Speaker (10W+10W), Wi-Fi Embedded |
|--------------------------|---|--------------------------------|---|
| Panel Technology | 60Hz (Slim Direct-LED Backlight) | | (802.11 a/b/g/n support), WiDi 2.0, Magic Clone |
| Resolution | 1920 x 1080 | | (to USB), Auto Source Switching & Recovery, Lamp Error Detection, Super Clear Coating, |
| Brightness (cd/m2) | 450 nits | | Temperature Sensor, RS232C/RJ45 MDC, Plug |
| Contrast Ratio | 4000:1 | | and Play (DDC2B), PIP/PBP, Video Wall (10x10), |
| Viewing Angle | 178°/178° | | Image Rotation, Button Lock, DP 1.2 Digital |
| Orientation | Landscape/Portrait | | Daisy Chain (Supporting 2x2 UHD Resolution, HDCP Support), Smart Scheduling, Smart F/W |
| Response Time | 6.5ms | | update, Built-In MagicInfo (Lite, Premium-S, |
| Inputs | 1 x VGA (D-Sub) 1 x DVI-D | | Videowall-S), SMART Signage Platform Compliant |
| | 1 x DisplayPort 1.2 | Dimensions (WxHxD) | 57.8" x 33.4" x 2.2" |
| | 1 x Component (CVBS common) 2 x HDMI | Weight | 60.3 lbs (27.41 kg) |
| | 1 x Stereo Mini Jack | Touchscreen Specifications: | |
| Outputs | 1 x DisplayPort 1.2 (Loop-out) | Model | CY-TE65 |
| | 1 x Stereo Mini-Jack | Connectivity Technology | Wired |
| External Control | RS232C (In/Out), RJ45 | Dimensions (WxHxD) | 59.1" x 34.7" x 2.5" |
| External Sensor | IR, Ambient Light Sensor | Weight | 48.9 lbs |
| Bezel Width | 18.0mm (Bottom 23.5mm) | Glass Thickness | 3.2" |
| | 15.8" x 15.8" (400 x 400mm) | Frame Material | Aluminum Extrusion |
| Mount Interface | | Bezel Width | 43.2mm |
| Power Requirement | 100 to 240 VAC (+/- 10 %), 50/60 Hz | Movement Detection | Infrared |
| Power Consumption | 230W (typical) 253W (max) | Technology | |
| | | Features | Glass display overlay, 6 point simultaneous touch |



24/7/365 Sales & Technical Support