Wireless presentation system for small to medium sized meeting rooms



Creativity is one of the core assets of your organization. With ClickShare, you can make sure ideas receive the attention they deserve. This wireless presentation system allows users to simply share what's on their laptop or mobile device, on the presentation screen. No cables, no set-up, no waiting to join in.

Plug in to stand out

The CSE-200 offers the ClickShare experience for small and medium-sized meeting rooms. Anyone – including guests – can connect with one click and share right away, without the need for any training. Users simply plug a USB-powered device – the ClickShare Button – into their PC or Mac and click the button to get the content from their laptop on the large meeting room screen. With the ClickShare App, users can also share content from their mobile phones or tablets.

Encouraging collaboration

The CSE-200 was designed for enterprise rollouts and offers enhanced security features, a wider range of connectivity options – including AirPlay and Google Cast support for non-HDCP content – and central management. Allowing up to 2 persons to share content simultaneously, the CSE-200 ensures direct connectivity to the central screen and encourages collaboration. For user convenience, security features of the CSE-200 can be set to one of three predefined levels, depending on the company's policies and needs. Last but not least, the device's API also makes integration into the company network a lot easier.



Product specifications

CSE-200

| • | |
|--|--|
| General specifications | |
| Operating system | Windows 7/8/8.1/10 Mac OSX 10.10/10.11 Android 4.1 and later (ClickShare app) iOS 7.0 and later (ClickShare app) |
| Video outputs | 1x HDMI |
| Frame rate | Up to 30 fps |
| Output resolution | 1920x1200 |
| Noise Level | Fanless |
| Number of sources simultaneous on screen | 2 |
| Number of simultaneous connections | 16 |
| Audio | Via HDMI, analog via Audio Jack 3.5mm, S/PDIF |
| iPad, iPhone and Android compatibility | Sharing of documents, browser, camera for both Android and iOS devices via ClickShare app |
| Extended desktop | Available (depending on the driver of your graphics card) |
| Authentication protocol | WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.1X in network integration mode |
| Wireless transmission protocol | IEEE 802.11 a/g/n |
| Reach | Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit |
| Frequency band | 2.4 GHZ and 5 GHz |
| Connections | 1x Ethernet LAN 2x (back) + 1x (front) USB Audio analog line out on mini jack socket (3.5mm), digital S/PDIF |
| Temperature range | Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) |
| Humidity | Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing |
| Anti-theft system | Kensington lock |
| Certifications | FCC/CE |
| Warranty | 3 years standard Possible to extend to 5 years |
| ClickShare Base Unit dimensions | |
| Dimensions (HxWxD) | 205mm x 115mm x 45mm (excl. antennas) / 8.1" x 4.5" x 1.8" 205mm x 150mm x 135mm (incl. antennas) / 8.1" x 5.9" x 5.3" |
| Power consumption | Operation: 6W (typical) / 18W (max) Standby: 2.6W (ECO standby) / 0.4W (Deep standby) |
| Weight | 600g / 1.32lbs |
| | |



