

# Product Spec Sheet from Rentex

## Panasonic Remote Camera Controller

Download Spec Sheet @ [www.rentex.com/spec/CAM2010.pdf](http://www.rentex.com/spec/CAM2010.pdf)

Rentex Product No. CAM2010



Mfr Part No. AW-RP50N

The Panasonic Remote Camera Controller uses serial and IP control to support Panasonic pan/tilt heads, integrated, and box cameras. Simple to set up and operate, the controller offers automatic IP setup and can be configured via your PC.

Using the Remote Camera Controller, you can control 1 camera simultaneously with up to 5 AW-RP50 via IP or serial control. It also allows you to control up to 100 AW-HE50S/H units via an IP connection when using a network hub (switching hub). The Automatic IP Address Setup function automatically assigns IP addresses to the AW-HE50S/H or AW-HS50 units. Camera functions including pan/tilt, zoom, focus, iris, gain, pedestal, shutter, white/black balance, and switch scene files can be adjusted remotely via the device.

### Features

- Can be configured via your PC
- Automatic IP Address Setup function
- Simple to set up and operate and offers automatic IP setup
- Uses serial and IP control to support up to 5 Panasonic pan/tilt heads, integrated, and box cameras

### Detailed Specifications

#### Remote Control

**Protocol** IPv4, RS-422 (Panasonic AW series protocol)

**Connection** Serial: Up to 5 cameras / IP: Up to 100 cameras (Up to 100 when Serial and IP are used together)

**Adjustment functions** Pan/Tilt, Zoom, Focus, Iris, Gain, Pedestal, Shutter, Detail, White Balance (Auto, R/B Gain), Black Balance (Auto, R/B Pedestal), Switch scene files

**Preset memory** Up to 100

#### Switcher Control

**Connection** IP: 1

**Switcher Supported** AW-HS50N

**Linkage** Camera information display, TALLY information imported, BUS material selection (AUX/PVW/PinP/KEY-F), Parameter changes (Pan/Tilt lever, Zoom button)

#### Interface

**TALLY/GPI** TALLY input x 5 channels, GPI INPUT x 4 channels, GPI OUTPUT x 4 channels, D-sub 15 pin (female x 1)

**LAN** 10BASE-T/100BASE-TX (for IP control), RJ45 x 1

**Pan/Tilt head** RS422 (for Serial control), RJ45 x 5

#### General

**Power Requirements** DC 12V ±10 % (AC adapter provided)

**Power Consumption** 2.0 A

**Weight** 2.42 lbs

**Dimensions (WxHxD)** 8.26 x 2.63 x 6.96"