Anchor AN-1000X Powered Monitor

Download Spec Sheet @ www.rentex.com/spec/SPK0100.pdf

Rentex Product No. SPK0100



Mfr Part No. AN-1000X

Features

- Reach Crowds of 400+
- RCA & 1/4" Line Inputs
- MIC/LINE Configurable XLR Input
- Magnetically Shielded
- 50 watt sound system with response from 65Hz 20kHz
- Bass and Treble controls
- Delivers up to 103 dB of clear sound
- 9.5 lbs, 5.25 x 8.4 x 9.0 inches (H x W x D)
- **Wall Mount and Speaker Stand Available**

Detailed Specifications

Rated Power 50 watts continuous @ 4Ù

Frequency Response 65 Hz - 20 kHz ± 3dB

Max SPL @ Rated Power 103 dB @ 1 meter

Balanced Input Mic / line configurable, female XLR,

switchable phantom power

Line Input Hi-Z, unbalanced, 1/4"-phone & RCA

Line Output Lo-Z, RCA, buffer isolated line-level

Speaker Output 8Ù, unswitched, 1/4"-phone

AC Power Requirements 110 - 125Vac, 50/60 Hz, 90W Max

Dimensions 5.25 x 8.4 x 9" (H x W x D)

Weight 9.5 lbs

