



SHURE®

Mfr No. ULXD4D
Rentex No. MIC0025

FEATURES

- Our rental kit includes: ULXD4D, (2) ULXD2/SM58, (2) ULXD1, Cables, Case

Available Bands:
G50 (470-534MHz)
H50 (530-554MHz)
L50 (632-696MHz)

The Shure ULXD4D Dual Channel Digital Wireless Receiver offers two channels of uncompromising audio quality, RF signal stability and efficiency, and advanced setup features in a single rack unit. Rugged, yet lightweight and compact, the all-metal chassis houses two independent receivers, each with its own audio and RF meters, gain control, and receiver outputs that can be either direct or summed for flexible signal routing.

RF Input	
Spurious Rejection	>80 dB, typical
Connector Type	BNC
Impedance	50 Ω
Bias Voltage	12 - 13 V DC, 170 mA maximum, per antenna
Audio Output	
Gain Adjustment Range	-18 to +42 dB in 1 dB steps (plus Mute setting)
Configuration	1/4" (6.35 mm): Impedance balanced (Tip=audio, Ring=no audio, Sleeve=ground) XLR: Balanced (1=ground, 2=audio +, 3=audio -)
Impedance	Impedance
Mic/Line Switch	30 dB pad
Phantom Power Protection	1/4" (6.35 mm): Yes XLR: Yes
Housing	Galvanized Steel
Dimensions (H x W x D)	7.75 in. x 6.75 in. x 1.65 in.
Weight	42.0 lbs without antennas