



**SHURE®**

Mfr No. ULXD4Q  
Rentex No. MIC0030

FEATURES

- Our rental kit includes: ULXD4Q, (4) ULXD2/SM58, (4) ULXD1, Cables, Case
- Available Bands:**  
G50 (470-534MHz)  
H50 (530-554MHz)  
L50 (632-696MHz)

The Shure ULXD4Q Quad Channel Digital Wireless Receiver offers four channels of uncompromising audio quality, RF signal stability, and advanced setup features in a space-efficient single rack unit. Rugged yet lightweight and compact, the 1RU all-metal chassis houses four independent receivers, each with its own audio and RF meters, gain control, and XLR outputs that can be either direct or summed for flexible signal routing.

RF Input	
Spurious Rejection	>80 dB, typical
Connector Type	BNC
Impedance	50 Ω
Bias Voltage	12 - 13 V DC, 170 mA maximum, per antenna
Audio Output	
Gain Adjustment Range	-18 to +42 dB in 1 dB steps (plus Mute setting)
Configuration	1/4" (6.35 mm): Impedance balanced (Tip=audio, Ring=no audio, Sleeve=ground) XLR: Balanced (1=ground, 2=audio +, 3=audio -)
Impedance	1/4" (6.35 mm): 100 Ω (50 Ω Unbalanced) XLR: 100 Ω
Mic/Line Switch	30 dB pad
Phantom Power Protection	1/4" (6.35 mm): Yes XLR: Yes
Housing	Galvanized Steel
Dimensions (H x W x D)	7.75 in. x 6.75 in. x 1.65 in.
Weight	42.0 lbs without antennas