

Pearl

LIVE VIDEO PRODUCTION

Switching
Streaming
Recording




epiphan video
capture • stream • record

Pearl™ is a production video switcher with live streaming and recording. Use the built-in scaler and video mixer to create custom picture in picture layouts from up to four HD video sources including IP cameras. Record your videos while simultaneously streaming four 1080p video streams at 30 fps.

VIDEO SOURCE

CAPTURE STREAM RECORD



Capture 4 HD sources

Output 4 streams



Choose from 3 models

Pearl

For portable live production.
Includes a hard-shell carrying case.



Pearl

RACKMOUNT™

All the same features of Pearl,
designed for installation in a rack.



Pearl

RACKMOUNT TWIN™

Two completely independent Pearl systems
for high density rack installation.




EPIPHAN LIVE

Simple to use monitoring and live switching between sources or layouts using Epiphan Live, a control interface designed for ease of use with touch screen devices.



Plug and play, or tweak to perfection

Let Pearl set everything for you automatically, or use the web-based Admin panel to configure bitrate, frame size, layouts and more!




Output video for local displays

Show any source or program channel at front of house or on a larger confidence monitor at up to 1080p.

Keep your recordings safe

Hold hundreds of hours of HD recordings and configure automatic file transfer to a local USB drive or network drives.






Capture 4 HD sources at once

Pearl can capture just about any HD video source you have. IP cameras, HDMI, SDI, VGA and analog audio support.

Stream to viewers everywhere

Stream using the built-in streaming server or out to any CDN. Have as many as four different 1080p streams at 30 fps – all from one Pearl!




Switch video sources live

Pearl is a video mixer! Use the touch screen or **Epiphan Live** interface to preview and change the live content.

Create custom layouts

Completely customizable, drag and drop layouts with cropping and image overlay support.



* Specifications are for Pearl and Pearl Rackmount. Pearl Rackmount Twin is comprised of two independent Pearl systems.

Video inputs	2 × SDI, 2 × HDMI™ (DVI), 2 × VGA
Audio inputs	2 × ¼" left/right TRS audio, SDI audio and HDMI audio
Video output	On-board touchscreen and 2 × DisplayPort for video output
Video switching	During live streaming and recording via the touch screen or web UI
Video encoding	Codecs: H.264, MPEG-4, Motion JPEG
	Bitrate: 100 to 9999 kbit/s
	Color resolution: 4:2:0
	Frame rate: 4 × 1080p streams at 30 fps each
Audio encoding	MP3, PCM and AAC (sampling 16 - 48 kHz, bitrate up to 320 kbps)
Network	1 × 10/100/1000 Ethernet port (RJ45)
Storage	Local hard drives 1 TB HDD (512 GB SSD for rackmount models)
	Local USB Automatic or manual copy via 2 USB 2.0 ports
	Network storage FTP server or copy via FTP, SFTP, SCP, RSYNC, CIFS
Recording formats	AVI, MP4, MOV or MPEG-TS
Control	Web UI, touch screen as well as comprehensive HTTP and RS-232 APIs
Product dimensions	Pearl: 10 ⅝" x 3 ¼" x 7 ⅜" (270 mm x 82 mm x 187 mm), 3.4 lbs (1.54 kg)
	Pearl Rackmount and Pearl Rackmount Twin: 19 ⅝" x 3 ½" x 10 ⅝" (498 mm x 89 mm x 270 mm), 12.1 lbs and 14.6 lbs (5.5 kg and 6.6 kg)

www.epiphan.com

Email: info@epiphan.com

North America +1-877-599-6581

International +1-613-599-6581

™ and © 2016 Epiphan Systems Inc. All rights reserved.

Epiphan, Epiphan Video, Epiphan Systems, its products names and logos are tradenames or trademarks of Epiphan Systems Inc. All other company, interface and product names and logos are trademarks or registered trademarks of their respective owners in certain countries. Product descriptions and specifications regarding the products in this document are subject to change without notice.

BR117-06