Product Spec Sheet from Rentex

AJA HA5-4K 4K HDMI to 4K SDI Mini-Converter

Download Spec Sheet @ www.rentex.com/spec/XVP2060.pdf

.4K

The HA5-4K 4K HDMI to 4K SDI Mini-Converter from AJA provides high quality conversion of 4K HDMI to 4K SDI via a quad-link 3G-SDI output at frame rates up to 50/60 fps. It also supports SD, HD, and 2K HDMI to SDI conversion as well. The HA5-4K automatically senses incoming HD/2K resolution HDMI signals and convert them to a single 3G-SDI output. Up to eight channels of HDMI embedded audio can be passed through to the SDI output, ensuring your audio is always in sync with the SDI signal. The HA5-Plus features a compact, portable, and rugged design and comes with a universal power supply with international plugs for use around the world.

Features

- 4K HDMI 1.4 Input
- 4x 3G-SDI Outputs
- Supports 4K and UHD Signals up to 60 fps .
- HD/SD Resolutions Supported .
- **Automatic Input Signal Detection** .
- **Embedded Audio Support**


Video Outputs:

3G-SDI 4 x 3G-SDI (Level A or B): 4096 x 2160p @ 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 3840 x 2160p @ 23.98, 24, 25, 29.97, 30, 50, 59.94, 60

1280 x 720p @ 50, 59.94, 60

2048 x 1080p @ 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 1920 x 1080p @ 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 1920 x 1080i @ 25, 29.97, 30

- 4096 x 2160p @ 23.98, 24, 25, 29.97, 30 3840 x 2160p @ 23.98, 24, 25, 29.97, 30
- HD-SDI 2048 x 1080p @ 23.98, 24, 25, 29.97, 30 1920 x 1080p @ 23.98, 24, 25, 29.97, 30 1920 x 1080i @ 25, 29.97, 30 1280 x 720p @ 50, 59.94, 60
 - Input HDMI embedded audio, 24-bit, 2-channel
- Output SDI embedded audio, 24-bit, 2-channel





(800) 545.2313 www.rentex.com

Boston | New York/NJ | Philadelphia | Washington D.C. | Orlando | Las Vegas | Dallas/Ft Worth | Chicago | Anaheim/LA

•

Mfr Part No. HA5-4K

Detailed Specifications

Video Input:

800.545.2313

