# KINO FLO DIVA-LITE

LED 20 DMX

The **Diva-Lite LED 20 DMX** from **Kino Flo** combines a popular, time-tested form factor with the latest in LED technology. The light offers a high CRI of 95 and variable color temperature from 2700 to 6500K with magenta/green hue control to match the spectral curves on different cameras and other light sources on the set. Flicker-free, full range dimming without color shift is also offered. The 25 x 13 x 6" Diva-Lite 20 offers manual onboard or DMX512 control of all of these functions. In fact, the fixture has a built-in Lumen Radio receiver for wireless DMX control. The Diva-Lite LED 20 DMX's 100-240 VAC make it ready for worldwide use



PLEASE CONTACT YOUR RENTEX SALES REPRESENTATIVE FOR RENTAL PRICING













DIMENSIONS WxHxD: 25" X 13" X 6"

WEIGHT: 14.5 LBS

# **Product Spec Sheet from Rentex**

### Kino Flo Diva-Lite LED 20 DMX

#### Download Spec Sheet @ www.rentex.com/spec/LIT0005-KIT.pdf

#### **Rentex Product No. LIT0005-KIT**



Mfr Part No. DIV-L20X-120U

## **Detailed Specifications**

The Diva-Lite LED 20 DMX from Kino Flo combines a popular, time-tested form factor with the latest in LED technology. The light offers a high CRI of 95 and variable color temperature from 2700 to 6500K with magenta/green hue control to match the spectral curves on different cameras and other light sources on the set. Flicker-free, full range dimming without color shift is also offered. The 25 x 13 x 6" Diva-Lite 20 offers manual onboard or DMX512 control of all of these functions. In fact, the fixture has a built-in Lumen Radio receiver for wireless DMX control. The Diva-Lite LED 20 DMX's 100-240 VAC make it ready for worldwide use.

#### **Features**

- 100-240 VAC, 24 VDC
- US/No.American Plug
- Variable Color: 2700 to 6500K
- Green/Magenta Hue Adjustment
- Wired and Wireless DMX
- CRI 95

**Light Source** LED

**Color Range** 2700 to 6500 K **Dimming** Yes, full range

**Mount** Lollipop with 5/8" (16 mm) receiver

**Connectivity** DC input: 3-pin XLR

DMX input: 5-pin XLR, DMX output: 5-pin XLR

**Photometrics** 508 fc @ 2.0' (0.6 m)

70 fc @ 6.0' (1.8 m) 18 fc @ 12' (3.6 m) 2409 lux @ 3.3' (1.0 m) 412 lux @ 8.2' (2.5 m) 164 lux @ 13' (4.0 m)

Operating Voltage 100-240 VAC or 24 VDC

**Power Consumption** 150 W

1.3 A at 120 VAC and 7 A at 24 VDC

**Dimensions** 25 x 13 x 6.0" (63.5 x 33 x 15 cm)

**Weight** 14.5 lbs (6.5 kg)

