


SOUNDMATE LISTENING SYSTEM

KIT AVAILABLE FOR RENT

The **Telex ST-300** is a personal and assistive listening wireless base transmitter featuring 17 user-selectable frequencies in the VHF band. The unit is equipped with a comprehensive set of front-mounted control buttons, a backlit LCD display, a headphone jack with an adjustable level knob for input signal monitoring and a peak reader on the LCD display for visual input monitoring. The **Telex SR-400** is a portable VHF 16-channel, frequency-agile receiver with clear reception and treble boost control for improved intelligibility and is designed for assisted listening applications.



17 USER-SELECTABLE
FREQUENCIES



BALANCED/MIC,
LINE OR 70 VOLT XLR
AS WELL AS
UNBALANCED
1/4" INPUT



WHAT'S IN THE KIT?

- (1) TELEX ST-300 Soundmate Transmitter
- (5) TELEX SR-400 Soundmate Receiver
- (5) TELEX HED-2 Soundmate Headset

RENTEX PRODUCT NO: COMTSA1

PLEASE CONTACT YOUR RENTEX SALES REPRESENTATIVE FOR RENTAL PRICING



24/7 SALES &
TECHNICAL
SUPPORT



SAME DAY
DELIVERY TO MOST
MAJOR CITIES



COMPETITIVE
RENTAL PRICING



A LARGE INVENTORY
OF HIGH-QUALITY
EQUIPMENT



A BEST-IN-CLASS
QC PROCESS

(800) 574.1702 www.rentex.com

RENTEX
Audio Visual & Computer Rentals "Since 1980"

— Rent from a Partner, Not a Competitor —

Product Spec Sheet from Rentex

SoundMate Listening System (Kit)

Download Spec Sheet @ www.rentex.com/spec/COMTSA1.pdf

Rentex Product No. COMTSA1

Kit Includes:

- TELEX ST-300 Soundmate Transmitter (1)
- TELEX SR-400 Soundmate Receiver (5)
- TELEX HED-2 Soundmate Headset (5)

The **Telex ST-300** is a personal and assistive listening wireless base transmitter, featuring 17 user selectable frequencies in the VHF band. The unit is equipped with a comprehensive set of front-mounted control buttons, a backlit LCD display, a headphone jack with an adjustable level knob for input signal monitoring, and a peak reader on the LCD display for visual input monitoring.

The **Telex SR-400** is a portable VHF 16-channel frequency-agile receiver with clear reception and treble boost control for improved intelligibility, designed for assisted listening applications.

Telex ST-300 VHF Wireless Personal Listening System Transmitter



Mfr Part No. F.01U.118.400

System Modulation FM

Frequency Range 72 - 76 MHz

Operating Range 300' (91 m)

Tuning Frequency Control Crystal, +/- .005% tolerance

Power 13 - 20 VDC/VAC; 115 VAC, 60 Hz; 300 mA

FCC License Part 15, B5DM508

Output 80 K μ V/m @ 3 m

Deviation +/- 25 kHz

Controls & Indicators 1 x Power Switch
2 x Up/Down Increment Buttons
1 x Set Button
1 x Headphone Monitor Volume Control Knob
1 x Backlit LCD Display

Connectors 1 x 3-pin XLR Female, Balanced Input
1 x 1/4" TS Phone, Unbalanced Input
1 x Screw-In BNC Antenna Connector
1 x 1/4" Stereo Headphone Out

Antenna 1 x Detachable Telescoping 1/4 Wave

Dimensions 1.8 x 7.6 x 5.9" (45 x 192 x 150 mm)

Weight 4.4lbs (2 kg)(shipping weight)

Telex SR-400 17-Channel Assistive Listening Receiver



Mfr Part No. F.01U.118.401

Type of Receiver Assistive Listening Receiver

RF Carrier Frequency Range 72 - 76 MHz

Approx. Working Range 300'

Overall Frequency Response 100 Hz - 10 kHz, (+/- 3dB)

Signal-to-Noise Ratio >60 dB

Of Channels 17

Type of Output(s) 1 x 1/8" Mini Jack

Headphone Monitoring 1 x 1/8" Mini

Power Requirements 2 x "AA" Batteries

Battery Type/Approx. Life Two (2) "AA" Batteries/30 Hours Alkaline, 10 Hours NiCad

Display Backlit On/Tuning Indicator

Mounting Options Belt or Pocket

Antenna Type Uses Earphone Wire

Dimensions (HxWxD) 4 x 2.75 x 1" (101 x 70 x 25mm)