YAMAHA QL5

32-INPUT, 16-OUTPUT DIGITAL MIXER

The Yamaha QL5 is an all-in-one mixing, processing and routing digital mixer with a 32 + 2 fader configuration that adapts to a wide range of channel layouts. The QL5's compact console footprint combined with large-scale capabilities makes it ideal for small to medium scale live sound performances, corporate events, installations, and much more



MIX CHANNELS: 64 MONO, 8 STEREO



BUSSES: 16 MIX, 8 MATRIX (INPUT TO MATRIX SUPPORTED)



LOCAL I/O: 32 IN, 16 OUT



FADER CONFIGURATION: 32 + 2 (MASTER)





STAINLESS STEEL IPAD SUPPORT STAYS

RENTEX PRODUCT NO: MXR6400

DIMENSIONS WxHxD: 32.6" X 10.7" X 22.2"

WEIGHT: 48.1 LBS

PLEASE CONTACT YOUR RENTEX SALES REPRESENTATIVE FOR RENTAL PRICING













— Rent from a Partner, Not a Competitor

Product Spec Sheet from Rentex

Yamaha QL5 64-Channel Digital Mixer



Mfr Part No. QL5
Rentex Product No. MXR6400

The acclaimed CL series raised live digital mixing console performance to an unprecedented level of refinement with evolved sound quality, operability, and functionality, while maintaining the traditional values that have made Yamaha digital mixers industry standards. Core features and performance inherited directly from the CL series, including natural sound supported by sonically superb internal processing capabilities, operation that easily adapts to the demands of just about any working environment, and built-in Dante networking that facilitates flexible system configuration, have now been condensed and concentrated into the compact QL series digital mixing consoles.

Features

- Pure, Natural Sound
- Powerful Built-in Processing for Broad Creative Control
- Refined Control for Smooth Operation
- Expandable All-In-One Support for Any Application

Detailed Specifications

Input Mixing Channels 64 mono + 8 stereo

Sampling Frequency Rate Internal: 44.1 kHz/ 48 kHz

External: 44.1 kHz

Signal Delay Less than 2.5 ms

Fader 100 mm motorized,

Resolution= 1,024 steps

Total Harmonic Distortion Less than 0.05%

Frequency Response +0.5, -1.5 dB 20 Hz- 20kHz

Dynamic Range 112 dB typ

Crosstalk -100 dB*1

Power Requirements 100-240 V 50/60 Hz

Power Consumption 200 W

Accessories Owner's Manual. Dust Cover,

Power Cord, DVS License Sheet,

Nuendo Live

Dimensions 32.6 x 10.7 x 22.2 inches (W x H x D)

Net Weight 48.1 lb

Equivalent Input Noise -128 dBu typ

Residual Output Noise -88 dBu

Display 10 inch Touch Panel

