ROLAND PRO A/V - V-60HD MULTI-FORMAT HD VIDEO SWITCHER

MULTI-FORMAT HD VIDEO SWITCHER

The V-60HD subrental simplifies your set-ups and combines the best of both worlds that includes SDI inputs for camera sources and scaled HDMI inputs for data, computer, tablet and other video sources. The combination of powerful audio features that include multi-channel embedded audio, XLR and RCA analog inputs, de-embedded audio from digital SDI or HDMI sources plus a variety of video connections with a Program and Aux Bus makes the V-60HD ideal for a variety of live event and production applications.



THE FOUR SDI INPUTS AND TWO HDMI INPUTS ARE PERFECT FOR SWITCHING CAMERAS AND COMPUTERS AT THE SAME TIME



8X MULTI-FORMAT CHANNELS; 6X INPUTS



THE V-60HD'S AUTO MIXING FUNCTION THAT WILL AUTOMATICALLY BALANCE AUDIO LEVELS FROM MULTIPLE MICROPHONES AND VIDEO SOURCES



NOT ALL CAMERAS SUPPORT FULL 1080P SO THE DE-INTERLACER ON THE SDI INPUTS ALLOWS YOU TO EASILY MIX AND MATCH 1080I AND 1080P SDI VIDEO SOURCES

XVS4075



DIMENSIONS WxHxD: 14¹/₄," X 3¹/₄," X 8³/₄" WEIGHT: 6.625 LBS

RENTEX PRODUCT NO:

PLEASE CONTACT YOUR RENTEX SALES REPRESENTATIVE FOR RENTAL PRICING





— Rent from a Partner, Not a Competitor –

Roland A/V - V-60HD Spec Sheet from Rentex Multi-Format HD Video Switcher

(800) 545.2313 www.rentex.com



Roland

Mfr No. V-60HD Rentex No. XVS4075

Live event and production continues to grow and the demand for more features • requires a sophisticated feature set. The V-60HD simplifies your set-ups and combines the best of both worlds that includes SDI inputs for camera sources and scaled HDMI inputs for data, computer, tablet and other video sources. The combination of powerful audio features that include multi-channel embedded audio, XLR and RCA analog inputs, de-embedded audio from digital SDI or HDMI sources plus a variety of video connections with a Program and Aux Bus makes the V-60HD ideal for a variety of live event and production applications.

FEATURES

- 8 x Multi-Format Channels; 6 x Inputs
- 4 x SDI Inputs with Deinterlace
- 2 x HDMI Inputs with Scalers
- 1 x RGB/Component Input Shared with HDMI
- 2 x SDI and 2 x HDMI Assignable Outputs
- Program, Preview, and Aux Outputs
 - 1 x HDMI Multiview Output
 - Smart Tally/GPI/RS-232 Interface
 - Embedded Audio and Analog Audio Inputs

Video Processing	YPbPr: 4:2:2, 8-bit
Audio Processing	Sampling Rate: 24-bit, 48 kHz
Interface	USB Type-A (for USB memory) Tally/GPI: DB-25, female (Tally: 12 / GPI: 8)RS-232: DB-9 male (for remote con trol) LAN: RJ45 100BASE-TX (for remote control)
Inputs	4 x SDI, BNC (inputs 1 to 4) 2 x HDMI type A (inputs 5 to 6)
Operation Temperature	32 to 104°F / 0 to 40°C
Power	AC power adapter
Functions	Memory (8 types) Panel lock EDID emulator
Display	Graphic LCD: 128 x 64 dots
Power Consumption	12 VDC 37 W 3.1 A
Dimensions (W x H x D)	14.0 x 8.7 x 3.8" / 35.6 x 22.1 x 9.6 cm
	14.0 × 6.7 × 5.6 7 55.0 × 22.1 × 5.0 cm









🕻 (800) 545.2313 🛛 🗃 www.rentex.com