

JBL PRX812

12" POWERED SPEAKER


The PRX812W from JBL is a two-way powered loudspeaker designed for main PA and monitor applications with extensive Wi-Fi control over the onboard DSP. The speaker utilizes two 750W Class-D amplifiers, delivering a total of 1500W to the 12" woofer and 1.5" compression driver, which combine to offer a frequency range of 52 Hz to 20 kHz at 135 dB maximum SPL output.



1500W, 12" 2-WAY
ACTIVE PA SPEAKER



ONBOARD WI-FI TECHNOLOGY
AND ADVANCED DSP OFFER
REMOTE SYSTEM OPERATION



12" WOOFER AND
1.5" COMPRESSION DRIVERS



FREQUENCY RESPONSE
58 HZ TO 20 KHZ



135 DB MAX
SPL OUTPUT

RENTEX PRODUCT NO: **SPK0420**
DIMENSIONS WxHxD: **15.1" X 23.6" X 13.4"**
WEIGHT: **42.5 LBS**

PLEASE CONTACT YOUR RENTEX SALES REPRESENTATIVE FOR RENTAL PRICING



24/7 SALES &
TECHNICAL
SUPPORT



SAME DAY
DELIVERY TO MOST
MAJOR CITIES



COMPETITIVE
RENTAL PRICING



A LARGE INVENTORY
OF HIGH-QUALITY
EQUIPMENT



A BEST-IN-CLASS
QC PROCESS

(800) 574.1702 www.rentex.com

RENTEX

Audio Visual & Computer Rentals

"Since 1980"

— Rent from a Partner, Not a Competitor —

JBL PRX812 Spec Sheet from Rentex

12" Powered Speaker

(800) 545.2313
www.rentex.com



Mfr No. PRX812W
Rentex No. SPK0420

FEATURES

- 1500W, 12" 2-way active PA speaker
- Onboard Wi-Fi technology and advanced DSP offer remote system operation
- 12" Woofer and 1.5" Compression Drivers
- Frequency Response 58 Hz to 20 kHz
- 135 dB Max SPL Output

The PRX812W from JBL is a 2-way powered loudspeaker designed for main PA and monitor applications with extensive Wi-Fi control over the on-board DSP. The speaker utilizes two 750W Class-D amplifiers delivering a total of 1500W to the 12" woofer and 1.5" compression driver, which combine to offer a frequency range of 52 Hz to 20 kHz at 135 dB maximum SPL output.

System Type	Self-Powered 12.0" / 30.5 cm, two-way, bass-reflex
Max SPL Level	135 dB peak
Input Connectors	2 x Balanced combo XLR-1/4" / 6.35 mm input 2 x unbalanced RCA input
Power Rating	1500 W (750 W x 2)
AC Power	100 to 240 VAC ~ 50/60 Hz
Dynamics	dbx Type IV limiter circuit
Crossover Frequency	1.850 kHz
Coverage Pattern	90 x 50° nominal
Suspension / Mounting	Dual 1.4" / 36.0 mm pole socket, 12 x M10 Suspension Points
Power Consumption	18 W (Typical) 0.3 W (Standby)
Transport and Storage	1 x injection-molded handle with back ing cup
Dimensions (H x W x D)	23.6 x 15.1 x 13.4"
Weight	42.5 lb / 19.3 kg



RENTEX
Audio Visual & Computer Rentals "Since 1980"

24/7/365 Sales & Technical Support

☎ (800) 545.2313

🌐 www.rentex.com