

BARCO IMAGE PRO 4K FROM RENTEX

VIDEO SCALER, SCAN CONVERTER
AND SWITCHER


The ImagePRO 4K easily scales, converts, and switches the highest quality signals, without latency, to ensure the smoothest images. With the latest I/O standards, HDMI 2.0, DP 1.2 and/ 3G-12G SDI signals are seamlessly converted for unparalleled flexibility.



4K 60P
RESOLUTION



4:4:4 SAMPLING,
10-BIT COLOR



LATENCY OF 1 FRAME,
PROGRESSIVE




OUTPUT IMAGE
ROTATION


MORE INFO:
[RENTEX.COM/RENTAL-PRODUCTS/BARCO-IMAGEPRO-4K/](https://rentex.com/rental-products/barco-imagepro-4k/)




RENTEX PRODUCT NO: **XVP1080**
DIMENSIONS HxWxD: **1.72" X 19.06" X 15.91"**
WEIGHT: **15.2 LBS**




CUSTOM LED
MODE



LATEST I/O CONNECTORS
INCLUDING
HDMI 2.0, DP1.2 AND 3G-12G SDI



FULL HDCP
COMPLIANCE



3 OPERATING MODES:
STANDARD PROGRAM, STANDARD
PREVIEW, AND MATRIX MODE

CONTACT YOUR REP FOR PRICING AND AVAILABILITY

24/7 SALES & TECHNICAL SUPPORT

SAME DAY DELIVERY TO MOST MAJOR CITIES

COMPETITIVE SUBRENTAL PRICING

A LARGE INVENTORY OF HIGH-QUALITY EQUIPMENT

A BEST-IN-CLASS QC PROCESS

(800) 574.1702 www.rentex.com

RENTEX

Audio Visual & Computer Rentals

— Rent from a Partner, Not a Competitor —

"Since 1980"



BARCO

Mfr No. R9004795
Rentex No. XVP1080

ImagePRO 4K easily scales, converts and switches the highest quality signals without latency (4K, 4:4:4, 60p, 10-bit) to ensure the smoothest images. The latest I/O standards, HDMI 2.0, DP 1.2 and 3G-12G SDI are seamlessly converted for unparalleled flexibility. Like all Barco's image processing products, the ImagePRO 4K is built to provide long-life performance both for fixed installs as well as for life on the road. What's more, the live-source view on the front panel provides a clear view of the incoming signal giving you the confidence you need to execute your event flawlessly.

Video Input	Factory-loaded with a Tri-Combo input card -supports 1x HDMI 2.0 4K60p 4:4:4 8bit, 4:2:2 10 bit, 1x DisplayPort 1.2 4K@60p 4:4:4 10bit, and 2x 12G SDI 4K@60p 4:2:2 10bit or 4x 3G SDI 1200p@60p 4:2:2 10bit
Video Output	Comes loaded from the factory with a Tri-combo output Card -supports 1x HDMI 2.0 4K60p 4:4:4 8bit, 4:2:2 10 bit, 1x DisplayPort 1.2 4K@60p 4:4:4 10bit, and 2x 12G SDI 4K@60p 4:2:2 10bit or 4x 3G SDI 1200P@60 4:2:2 10 bit
Still stores	Up to 100 HD or 25 UHD. Import file size dependent
Multiviewer	Video preview on front panel
Expandability	Future support for 2nd generation Event Master input and output cards (limited functionality on non-Tri-Combo cards).
Dimensions	Height: 1.72" (4.37 cm) 1 RU Rack mount Width: 19.06" (48.41 cm) Incl. rack mount Depth: 15.91" (40.41 cm)
Power	Input power: 100-240 VAC 50/60Hz 125w
Weight	15.2 pounds (6.8 Kg)

FEATURES

- 4K 60P resolution
- 4:4:4 sampling, 10-bit color
- Latency of 1 frame, progressive
- Latest I/O connectors including HDMI 2.0, DP1.2 and 3g-12G SDI
- Output image rotation
- Custom LED mode
- Full HDCP Compliance
- 3 Operating Modes (Standard program, Standard Preview and Matrix mode)

