



Mfr No. 7413A1001
Rentex No. LITFECS

FEATURES

- 19, 26, 36, and 50 degree EDLT barrels available
- New RGB-L LED array made of red, green, blue, and lime emitters
- Terminated to Edison
- Simple user interface with three-button control and a seven-segment display
- 12 customizable presets and five sequences
- DMX/RDM input and thru (5-pin XLR)

The ColorSource Spot outperforms other four-color LED profiles, thanks to its precise combination of red, green, blue and lime emitters. ETC applied its extensive color-mixing knowledge to the fixture to ensure that it can achieve brighter, richer and more believable colors than other budget LEDs. And it accepts all the Source Four LED accessories, zoom and fixed-focus lens tubes, and CYC and Fresnel adapters.

Light Source	60 x Luxeon Rebel LED emitters (RGB-L: red, green, blue, lime)
Display/Controls	3-button, 7-segment display 12 x customizable presets (local control) 5 x sequences (local control)
Protocols	DMX512, RDM
DMX Channel Modes	1 x Mode: 5 channels DMX Profile: intensity, red, green, blue, strobe (IRGBS)
DMX Connectors	1 x XLR 5-pin DMX input 1 x XLR 5-pin DMX thru
Power	100 to 240 VAC, 50/60 Hz (universal)
Power Connectors	1 x powerCON input 1 x powerCON output
Power Linking	10 x units (per circuit)
Power Consumption	100 VAC (RGB Full): 148 W, 1.48 A 120 VAC (RGB Full): 147 W, 1.24 A 230 VAC (RGB Full): 141 W, 0.65 A
Inrush Current	120 VAC: 28 A 240 VAC: 46 A
Dimensions	23.33 x 13.36 x 26.44" (59.3 x 33.9 x 67.2 cm)
Weight	17 lb

