


# QSC CP12 Spec Sheet from Rentex

## 12" Compact Powered Loudspeaker

(800) 545.2313  
www.rentex.com



Mfr No. CP12-NA  
Rentex No. SPK0240

The QSC CP12 is a compact powered loudspeaker suitable for portable or in stalled live-sound applications. The monitor gives you the ability to mix up a mic/line input, a line input, and a music playback device, supplying a total of three inputs. The QSC CP12 is capable of handling up to 1000W peak thanks to its Class-D amplifier, doing so through its 12" cone LF transducer and 1.4" HF compression driver. It allows you to reach SPL values of up to 126 dB, and the construction of the monitors ensures an even frequency response from 49 Hz to 20 kHz.

Configuration	2-way active loudspeaker
Transducers	LF Driver: 12.0" / 305.0 mm, cone HF Driver: 1.4" / 35.6 mm, compression driver
Frequency Response	49 Hz to 20 kHz at -6 dB 47 Hz to 20 kHz at -10 dB
Max SPL	126 dB measured at 3.3" / 1.0 m with dynamic pink noise
Amplifier Class	Class-D
Controls	Power, gain, mic boost, 6-way contour selector
Connectors	2 x XLR-1/4" combination input (line input and mic/line input, locking) 1 x 3.5 mm TRS input 1 x XLR output (mix output)
AC Power	Universal power supply, 100 to 240 VAC, 50 to 60 Hz
AC Power Consumption	100 VAC, 0.75 A / 120 VAC, 1.0 A / 240 VAC 0.31 A (at 1/8 power)
Response Time	8 ms
Dimensions (W x H x D)	20.3 x 13.8 x 12.7"
Weight	30.3 lb

### FEATURES

- 12" 800W Woofer, 1.4" 200W Driver
- 49 Hz to 20 kHz Frequency Response
- Max SPL of 126 dB
- Light weight and highly portable
- Class-D Power Amplifier
- Combo XLR Inputs & 3.5mm Playback Input
- One-Touch +25 dB Boost Switch on Input B



**RENTEX**  
Audio Visual & Computer Rentals "Since 1980"

**24/7/365 Sales & Technical Support**

(800) 545.2313

www.rentex.com