


PANASONIC PT-RZ120


12,000 LUMENS 1-CHIP DLP LASER PROJECTOR

12,000 LUMENS 1-CHIP DLP
LASER PROJECTOR

The 12,000 lm*1 Panasonic PT-RZ120 is a first among 1-Chip DLP™ projectors. Further refinements to Panasonic's high-quality imaging technology and filterless cooling system result in uncommonly high brightness from a compact body. Expect vibrant, high-contrast pictures and consistent color uniformity across multiple screens courtesy 1-Chip DLP™ technology and dual solid-state laser light engines.



HIGH BRIGHTNESS
AND EXCELLENT
IMAGE QUALITY
WITH LASER LIGHT
SOURCE



10,000 :
1 CONTRAST RATIO



4K INPUT AVAILABLE
(HDMI/DIGITAL LINK)



LASER 1-CHIP
DLP, 12,000 ANSI
LUMENS, WUXGA



RENTEX PRODUCT NO: 7120
DIMENSIONS HxWxD: 7.88" X 19.59" X 22.88"
WEIGHT: 51.9 LBS

PLEASE CONTACT YOUR RENTEX SALES REPRESENTATIVE FOR SUBRENTAL PRICING



24/7 SALES &
TECHNICAL
SUPPORT



SAME DAY
DELIVERY TO MOST
MAJOR CITIES



COMPETITIVE
SUBRENTAL PRICING



A LARGE INVENTORY
OF HIGH-QUALITY
EQUIPMENT



A BEST-IN-CLASS
QC PROCESS

RENTEX

Audio Visual & Computer Rentals

"Since 1980"

(800) 574.1702 www.rentex.com

— Rent from a Partner, Not a Competitor —



Mfr No. PT-RZ120B
Rentex No. 7120

FEATURES

- Laser 1-chip DLP, 12,000 ANSI lumens, WUXGA
- High brightness and excellent image quality with laser light source
- 4K Input available (HDMI/DIGITAL LINK)
- Lens Options: 0.38:1 HD, 0.78-0.98:1 HD, 0.99-1.32:1 HD, 1.3-1.8:1 HD, 1.7-2.4:1 HD, 2.5-4.0:1 HD, 3.7-5.7:1 HD, 5.7-8.0:1 HD

The 12,000 lm*1 Panasonic PT-RZ120 is a first among 1-Chip DLP™ projectors. Further refinements to Panasonic’s high-quality imaging technology and filterless cooling system result in uncommonly high brightness from a compact body. Expect vibrant, high-contrast pictures and consistent color uniformity across multiple screens courtesy 1-Chip DLP™ technology and dual solid-state laser light engines.

| | |
|---|---|
| Projector type | 1-Chip DLP™ projector |
| Light source | Laser Diode |
| Light output | 12,000 lm*1 / 12,600 lm (Center)*2 |
| Resolution | 1920 x 1200 pixels |
| Center-to-corner uniformity*1 | 90% |
| Time until light output declines to 50%*3 | 20,000 hours (NORMAL)/24,000 hours (ECO) |
| Contrast*1 | 10,000:1 (Full On/Full Off, Dynamic Contrast Mode: 3) |
| Screen size (diagonal) | 1.27–15.24 m (50–600 in), 1.27–5.08 m (50–200 in) with ET-DLE055, 2.54–8.89 m (100–350 in) with ET-DLE035, 16:10 aspect ratio |
| Power supply | AC 100–240 V, 50/60 Hz |
| Power consumption | 1,100 W |
| Operation noise | 44 dB (Normal)/41 dB (Quiet1)/38 dB (Quiet2) |
| Dimensions (W x H x D) | 19 19/32" x 7 7/8" *5 x 22 7/8" |
| Weight | Approximately 51.9 lbs |

