



# Panasonic

**Mfr No. AW-RP150GJ**  
**Rentex No. CAM2065**

### FEATURES

- Large touchscreen for easy usability
- New joystick for one-handed operation
- Simplified PTZ camera presets and tracing memory
- Intuitive design elements based on direct feedback from everyday robotic camera operators
- 3G-SDI Active Through Output, 5 x RS-422, LAN PoE+, 2 x GPIOs

The AW-RP150 is the newest remote camera controller to compliment Panasonic's comprehensive professional PTZ camera lineup. It has the same great functionality as Panasonic's existing controllers, but includes a new one-hand operation joystick (controlling PTZ or Focus) and a large touch-panel LCD screen for monitoring and menu setting. A seesaw lever mounted on the joystick manages pan and tilt operations for zoom and focus control and intuitive single-handed operation. The built-in touch display allows for easy and quick operation of all essential camera functions.



Power Requirements	12 V DC (10.8 V to 13.2 V)
PoE++	IEEE802.3at standard: DC 42 V to 57 V (Camera Input)
Current consumption	1.0 A (Connector Input) 0.6 A (PoE+ power supply)
LCD Display	7-inch Touch Panel GUI Monitor (WVGA (800x480))
Pan / Tilt Speed Adjustment	7 levels
SD Memory Card slot	SDHC / SDXC Memory Card Slot x 1
Controller Supported Equipment	IP/RS422 AW-UE150W/K, AW-HR140*1, AW-HE130W/K*1, AW-HN130W/K*1, AW-UE70W/K*1, AW-UN70W/K*1, AW-HE40 Series*1, AW-HN40HW/HK*1, AW-HE38HW/HK*1, AW-HN38HW/HK*1
No. of Connectable Cameras	200 (IP), 5 (RS422)
Weight	Approx. 7.05 lb
Dimensions (H x W x D)	13-15/32 inches x 7 inches x 9-21/32 inches (excluding protrusions)