



ROSS VIDEO CARBONITE BLACK SOLO 1 M/E

LIVE PRODUCTION VIDEO SWITCHER FRAME


The Ross Video Carbonite Black Solo 1 M/E Live Production Video Switcher is an HD/SD video production switcher providing versatile switching in a highly portable format. Supporting multi-format video resolutions up to 1080p60, the Solo system incorporates nine inputs including six SDI and three HDMI, and six outputs including five SDI and one HDMI. The I/O frame and CB9 panel allow flexibility in the field, so you can locate the I/O and panel separately as needed.




OUTPUTS: 5 X SDI,
1 X HDMI



6 FRAME SYNC & FORMAT
CONVERTERS FOR
INPUT FLEXIBILITY



INPUTS: 6 X SDI,
3 X HDMI



SUPPORTS UP TO
1080P60 VIDEO



INCLUDES 2 MINI-ME FOR
MULTI SCREEN EVENTS

RENTEX PRODUCT NO: **XVS5000**

PLEASE CONTACT YOUR RENTEX SALES REPRESENTATIVE FOR RENTAL PRICING



24/7 SALES &
TECHNICAL
SUPPORT



DELIVERY TO MOST
MAJOR CITIES



COMPETITIVE
RENTAL PRICING



A LARGE INVENTORY
OF HIGH-QUALITY
EQUIPMENT



A BEST-IN-CLASS
QC PROCESS

(800) 574.1702 www.rentex.com

RENTEX
Audio Visual & Computer Rentals "Since 1980"

— Rent from a Partner, Not a Competitor —



Mfr No. CB-SOLO
Rentex No. XVS5000

FEATURES

- Inputs: 6 x SDI, 3 x HDMI
- Outputs: 5 x SDI, 1 x HDMI
- Includes 2 mini-me for multi screen events
- 6 frame sync & format converters for input flexibility
- Supports up to 1080p60 Video

The **Ross Video Carbonite Black Solo 1 M/E Live Production Video Switcher** is an HD/SD video production switcher providing versatile switching in a highly portable format. Supporting multi-format video resolutions up to 1080p60, the Solo system incorporates nine inputs including six SDI and three HDMI, and six outputs including five SDI and one HDMI. The I/O frame and CB9 panel allow flexibility in the field, so you can locate the I/O and panel separately as needed.



Direct Access Buttons	9
ME Number	1 x MEs 2 x MiniMEs 1 x ME rows 5 x Keys per ME (4 + 1 transition key) 2 x Keys per MiniME
Macros	36 x Custom control macros
Keys	9 x Total keys 1 x UltraChrome keyer
Media File Requirements	BMP, JPG, JPEG (no Alpha), TGA and PNG (with Alpha), and 48 kHz WAV audio files
Inputs	6 x SDI 3 x HDMI
Outputs	5 x SDI 1 x HDMI
Reference Input	Black or tri-level
Ports	1 x RS-422, editor port
Signal Processing	3G 1080p: 50/59.94/60 1080p: 29.97 1080PsF, 23.98/25 1080i: 50/59.94 720p: 50/59.94 576i: 50 480i: 59.94