



Mfr No. DMON-16S
Rentex No. XVP1790

FEATURES

- 1 to 16 Channel Multi-Viewer/Multi-plexer
- 16x SD/HD/3G-SDI Active Loop Through
- 16-1 Channel Multiplexer
- LCD Menu Access (No Need for Computer)

Featuring 16 independent 3G/HD/SD-SDI inputs, the DECIMATOR DMON-16S Multi-Viewer can be used either as a 1-to-16-channel multi-viewer or 16-to-1-input multiplexer supporting up to 1080p@60/59.94/50Hz on input and output. A miniature multi-viewer with front-panel LCD menu access, the DMON-16S is suitable for both on-location and studio applications, as you won't need to use a computer or DIP switch to make selections and adjust settings.

SDI Input & Output Formats	3G (SMPTE 424M@2.97 Gbps and 2.967 Gbps): 1080p at 60/59.94/50 Hz HD (SMPTE 292M/274M/296M@1.485 Gbps and 1.435 Gbps 1080p/psf at 30/29.97/25/24/23.98 Hz 1080i at 60/59.94/50 Hz 720p at 60/59.94/50/30/29.97/25/24/23.98 Hz SD (SMPTE 259M@270 Mbps) 525i at 59.94 Hz 625i at 50 Hz
HDMI Output Formats	1080p at 60/59.94/50/30/29.97/25/24/23.98 Hz 1080i at 60/59.94/50 Hz 720p at 60/59.94/50/30/29.97/25 Hz 525i at 59.94 Hz 625i at 50 Hz
Inputs	16x 3G/HD/SD-SDI on BNC (embedded audio support)
Outputs	1x 3G/HD/SD-SDI on BNC 1x HDMI Type-A
LED Indicators	Power Signal Lock and Rate: 6 x
Power	5 to 32 VDC Pin Pos Connector
Dimensions (W x D x H)	8.7 x 4.1 x 1.2" / 220 x 103.7 x 29.5 mm

