

## Featured Products of the Month

### Epiphan Pearl 2 Production Switcher



- Reliable, simple, live streaming
- Connect up to six sources at once to encode and stream one 4K Ultra HD program, or up to six 1080p Full HD programs
- Use video sources connected to the HDMI, 4K HDMI, or 12G-SDI video input ports, or from IP cameras
- Combine, crop, and scale up to six video sources

### Yamaha QL5 32-Input, 16-Output Digital Mixer



- Mix channels: 64 mono, 8 stereo
- Busses: 16 mix, 8 matrix (Input to Matrix supported)
- Local I/O: 32 in, 16 out
- Fader configuration: 32 + 2 (Master)
- Stainless steel iPad support stays

### Panasonic PT-RQ22K 20,000 Lumens 3-Chip DLP Laser Projector



- Bright and Vivid Picture Quality
- Cage Included (ET-PFD565)
- Compatible with D75LE and D3LE lenses
- 2560x1600 native resolution - 5120x3200 with Quad Pixel Drive ON

### Roland V-1HD Portable 4 x HDMI Input Switcher



- 4 x HDMI Inputs with Frame Buffers
- Hardware or PC Control
- 12-Channel Digital Audio Mixer
- Manual T-Bar
- Program Output and Multi-View Preview

### Roland Pro A/V – V-60HD HD Video Switcher



- The four SDI inputs and two HDMI inputs are perfect for switching cameras and computers at the same time
- Not all cameras support full 1080p so the de-interlacer on the SDI inputs allows you to easily mix and match 1080i and 1080p SDI video sources

### Shure AD4D Axient Wireless Mic System - Dual Channel



- Comprehensive remote control of all transmitter parameters
- Continuously monitor, evaluate, prioritize, queue and assign compatible UHF frequencies
- Seamless, uninterrupted audio through simultaneous transmission on two independent frequencies

### Panasonic TH-75EQ1 4K LCD Professional Display



- 4K ultra HD resolution delivering the highest detail and image quality
- Simple signage with built in USB media player
- Synchronized playback on multiple displays via USB and LAN
- Extensive connectivity features. 4K/60p video input signals via 2 x HDMI

### Amplivox Sound “H” Style Frosted Acrylic Floor Lectern



- 55.0 x 38.0 x 30.0” Case Dimensions (LxWxH)
- Stands 47 ½” inches high with a unique “H” design
- Built to perform, with solid construction, sturdy base, ergonomic designs and oversized reading surfaces
- Available in our local markets

## TRT Transtech I-Poster 1.9

### LED iPoster Screen



- Slim appearance, attractive display
- 74.8” high by 22.5” wide
- High refresh rate of 2.88kHz
- 160° viewing angle
- Packaged in cases of 4
- 1.9mm pixel pitch (high resolution)
- Standard “kickstand” included. Optional upright base available.



bracket standing



base standing installation

**Rent from a Partner, Not a Competitor**