



SHURE ULXD8

WIRELESS GOOSENECK BASE TRANSMITTER


The **ULXD8 Gooseneck Base Transmitter** offers a flexible gooseneck mic form factor that is ideal for use at meetings and events where wired microphones are impractical. Paired with a ULX-D or QLX-D digital receiver, the ULXD8 creates a system with low latency, long transmission range, and high channel count, delivering exceptional performance in large meeting venues where live sound reinforcement is required.




9 HOURS OF BATTERY LIFE
(ACCEPTS ALKALINE AA OR
RECHARGEABLE, RENTEX
PROVIDES ALKALINE AA)



300' (100M)
TRANSMISSION RANGE



COMPATIBLE WITH ULX-D
AND QLX-D SYSTEMS
(RENTEX CARRIES G50 BAND)



PERFECT FOR ACRYLIC
LECTERNS WITH
NO WIRING



AES256 ENCRYPTION
FOR SECURE
TRANSMISSION

RENTEX PRODUCT NO: **MIC0600**

PLEASE CONTACT YOUR RENTEX SALES REPRESENTATIVE FOR RENTAL PRICING



24/7 SALES &
TECHNICAL
SUPPORT



SAME DAY
DELIVERY TO MOST
MAJOR CITIES



COMPETITIVE
RENTAL PRICING



A LARGE INVENTORY
OF HIGH-QUALITY
EQUIPMENT



A BEST-IN-CLASS
QC PROCESS

(800) 574.1702  www.rentex.com

RENTEX

Audio Visual & Computer Rentals

"Since 1980"

— Rent from a Partner, Not a Competitor —



SHURE®

Mfr No. ULXD8
Rentex No. MIC0600

The ULXD8 Gooseneck Base Transmitter offers a flexible gooseneck mic form factor that is ideal for use at meetings and events where wired microphones are impractical. Paired with a ULX-D or QLX-D digital receiver, the ULXD8 creates a system with low latency, long transmission range, and high channel count, delivering exceptional performance in large meeting venues where live sound reinforcement is required.

Gain Adjustment Range	0 to 21 dB (in 3 dB steps)
Battery Type	Shure SB900/SB900A Rechargeable Li-Ion or AA batteries 1.5 V
Battery Runtime	@ 10 mW Shure SB900 Up to 9 hours AA batteries Up to 8 hours 20 minutes
Dimensions (H x W x D)	5.39 in. x 3.08 in. x 1.60 in.
Weight	293 g with AA batteries
Operating Temperature Range	0°C (32°F) to 45°C (113°F)
Housing	Molded Plastic
Audio Input	
Microphone Connector	6-pin connector for Shure MX405/10/15
Configuration	Unbalanced
Impedance	>20 kΩ
RF Output	
Antenna Type	Integrated PIFA
Impedance	50 Ω
Occupied Bandwidth	<200 kHz
Power	1 mW, 10 mW, 20 mW

FEATURES

- Compatible with ULX-D and QLX-D systems (Rentex carries G50 band) TRI-
- 9 hours of battery life (accepts Alkaline AA or rechargeable, Rentex provides Alkaline AA)
- 300' (100m) transmission range
- Perfect for acrylic lecterns with no wiring
- AES256 Encryption for secure transmission

