



A 12G-SDI, All-in-one Router with front panel buttons and Preview display. Simultaneously connect and route any combination of SD, HD and Ultra HD video, all the way up to high frame rate 2160p60, all on the same router at the same time! You also get revolutionary new visual routing that lets you see your router connections as video on the built in LCD as you scroll the knob to select your routing. Now you can route your video simply by looking at the video!

SDI Video Input	40 x 10-bit SD/HD/6G/12-SDI
SDI Video Output	40 x 10-bit SD/HD/6G/12-SDI
Reference Input	Blackburst and TriSync for SD, HD and UHD 4K
Multi-Rate Support	Auto detection of SD, HD, 6G or 12G-SDI. Simultaneous routing of 4K, HD, SD video and DVB-ASI
Control	40 buttons for local control of Videohub 6 buttons and scroll wheel for control of LCD display 1 x RJ45 Ethernet 1 x RS-422 input for controlling router crosspoint switching
SDI Compliance	SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 310M, SMPTE 425M Level B, SMPTE 425M Level A, ITU-R BT.656, and ITU-R BT.601
Display	5" (12.7 cm) LCD for video and menu settings
Power Supply	IEC power cables required 2 x 90 to 240 VAC input (for redundancy)
Weight	18.97 x 3.46 x 6.29" (48.18 x 8.79 x 15.98 cm)
Dimensions (H x W x D)	9.35 x 4.07 x 1.38" / 23.75 x 10.34 x 3.51 cm

- FEATURES
- Route any SDI Conforming signal up to 12G SDI
 - Control quickly from front-panel buttons or by Ethernet
 - Preview video sources right on the front panel
 - Add names for inputs and destinations, not just numbers

