



Mfr No. UM2

Rentex No. XADI400

The U-PHORIA UM2 2x2 USB Audio Interface from Behringer is a 2x2 USB audio interface that is capable of tracking your audio with a sampling rate up to 48 kHz. It features a single XENYX combination XLR/TRS microphone preamplifier with selectable 48V phantom power. Additionally, the UM2 has a front-panel 1/4" instrument input with dedicated level control. Output is provided in the form of stereo RCA outputs and a front-panel 1/4" headphone jack. The UM2 has selectable direct monitoring and is housed in a metal chassis to be impact resistant.

Channels of I/O	2 Inputs / 2 Outputs
Host Connection	1 x USB Type-B (USB 2.0)
Max Sample Rate/Resolution	48 kHz / 24-Bit
Max Input Level	Mic Inputs: +2 dBu Line Inputs: +22 dBu Hi-Z Inputs: +2 dBu
Max Output Level	Outputs: 0 dBu
Dynamic Range	100 dBA
Impedance	Mic Inputs: 3 Kilohms Hi-Z Inputs: 1 Megohm
Sample Rates	32 / 44.1 / 48 kHz
OS Compatibility	macOS 10 Windows XP or Later
Power Requirements	USB Bus Power
Power Consumption	2.5 W (Maximum)
Dimensions	5.1 x 4.7 x 1.8" / 129.54 x 119.38 x 45.72 mm
Weight	0.6 lb / 0.3 kg

### FEATURES

- Up to 48 kHz resolution
- Compatible with recording software including Avid Pro Tools, Ableton Live, Steinberg Cubase, and others
- Streams 2 inputs / 2 outputs with low latency to your computer, supporting Mac OS X and Windows XP or higher
- USB port for connection and power
- +48 V-powered XENYX mic preamp

