

Featured Products of the Month



Telescript PRS-150

Presidential Teleprompter System

- Kit Includes: (2) Teleprompters | Telescript AV Prompting Software with optional laptop
- Lightweight VESA Compatible Base Plate
- Professional HighBrite 15" Monitor with Standard 1000 nits, SDI, HDMI, VGA, Component & NTSC/PAL Composite inputs
- Unique Split Pole and Extension Design



Green Extreme T300 HD

1080p Webcam

- Full HD (1080p) resolution webcam
- Built-in Microphone
- Plug and Play simplicity to Windows and Mac PC's
- Enlivens popular conferencing and social software like Zoom, MS Teams, Skype, GoToMeeting, WebEx, and Instagram, plus sparks life into broadcast events and production of web content for YouTube



GVM 560AS

Variable White LED Light Panel

- Variable White (2300K-6800K)
- Dimmable
- CRI Of 97
- 30W
- Wireless Control Via APP (IOS, Android)



Sennheiser MKE 600

Shotgun Microphone

- Pronounced directivity
- Maximal rejection of side noise
- Switchable "Low Cut" filter minimizes wind noise
- Phantom or battery powering
- Battery switch with "Low Batt" indicator
- Accessories: [Rycote InVision On-Camera Shockmount](#), [Rycote Extension Handle](#), Rycote 18cm Classic Souffle, [On-Stage Microphone Boom Pole](#)



Teradek Cube 755 (TX)

Portable Stream Encoder

- HEVC (H.265) & AVC (H.264)
- Max Resolution: 1080p60
- Up to 30 Mbit/s
- Supports RTMP, RTSP, SRT, MPEG-TS and TDS (Teradek Streaming)
- Dual-Band 2.4/5.8 GHz WiFi, Ethernet and USB Interfaces
- HDMI and SDI Video Inputs
- Camera Top Form Factor
- Built-In Color Grading



Teradek Cube 775 (RX)

Portable Stream Decoder

- HEVC (H.265) & AVC (H.264)
- Up to 1080p60
- SDI & HDMI Output
- Supports RTSP, SRT, MPEG-TS and TDS (Teradek Streaming)
- Dual-Band 2.4/5.8 GHz WiFi, Ethernet and USB Interfaces
- HDMI and SDI Video Inputs
- Camera Top Form Factor
- Built-In Color Grading



Marantz AVS

All-In-One AV Web Broadcast System

- HD Webcam (H.264 video compression) w/ fixed-focus lens & manual pan and tilt capabilities
- USB condenser boundary microphone (48kHz/16bit)
- Dimmable LED ring light w/ diffusion filters
- USB-C output for low-latency computer connection
- (2x) USB 3.0 for external device connection



Decimator Design 12G-CROSS

4K HDMI/SDI Cross Converter and Scaler w/ Sync

- Up to 4K HDMI & 12G-SDI Input and Output
- Converts HDMI to SDI & SDI to HDMI (simultaneous operation)
- Built in scaler for up or down scaling
- Genlock port for sync

ikan PT4700-SDI



17" High Bright Beamsplitter On-Camera Teleprompter

- Monitor (4:3 Aspect Ratio) with 3G-SDI, HDMI, and VGA Inputs
- 1000 cd/m² Monitor with Image Flip
- Three Mounts for Compact to ENG Cameras
- 70/30 Beamsplitter Glass
- Adjustable sliding base for easy balancing

Rent from a Partner, Not a Competitor