

TRULUX P1.8 X-POSTER

PRODUCT SPECS

PHYSICAL DIMENSIONS

- **LENGTH 630 mm**
 - 24.80 in (approx. 24 13/16")
- **DEPTH 42.6 mm**
 - 1.68 in (approx. 1 11/16")
- **HEIGHT 2055 mm**
 - 80.91 in (approx. 80 7/8")

TECHNICAL SPECIFICATIONS

- **CABINET** Die-cast aluminum
- **OVERALL SIZE** 630 x 42.6 x 2055 mm (L x W x H)
- **SCREEN SIZE** 600 x 2025 mm (W x H), GOB
- **MODULE SIZE** 300 x 168.75 mm
- **PCB / SCAN** 4-layer PCB board; 1/30 scanning; standard LED
- **BRIGHTNESS** 600 nit
- **REFRESH RATE** 3840 Hz
- **POWER** Wide voltage 100-240V; UL-certified power supply
- **CONNECTIVITY** WiFi control and hard connection
- **CONFIGURATION** Supports splicing multiple posters together
- **LED PROTECTION** GOB



SEAMLESS poster cascade up to 6

TRULUX P1.8 X-POSTER

TECHNICAL PARAMETERS

Model	P1.8
Pixel Pitch(mm)	1.875
Module Size(mm)(WxH)	300x168.75
Module Resolution(dots)	160x90
Screen Display Size(mm)	600x2025
Screen Resolution(dots)	320x1080
Total Size(mm)(With frame)	630x2055x42.6
Weight(kg/screen)	52
Grey Scale(bits)	14
Refresh Rate(Hz)	≥3840
Contrast Rate	6000:1
Brightness(nits)	0-800（10-level adjustment）
Viewing Angle(H°/V°)	160°/160°
Operating System	Android
Video Interface	HDMI*2(1 Input & 1 Output),USB2.0*2
Audio Interface	External Audio Interface
Video Format	MP4,AVI,WMV,etc.
AC Input Power Max./Avg.(W/screen)	Max.520W/Avg.155W
Control Interface	RJ45,WIFI,AP Local Network,4G/5G Network(Optional)
Installation/Maintenance	Standing(Standard)/Stacking(Optional)/Hanging(Optional)/Wall Mounting