

URP652

4K LCD Display

The Planar® URP652 is a 65" 4K LCD display ideal for a wide range of applications ranging from dynamic digital signage to collaborative meeting spaces. It supports native 4K (3840 x 2160) resolution at up to 60Hz via HDMI® 2.1 and DisplayPort 2.0, enabling smooth motion video and mouse tracking. Users can view up to four sources simultaneously and receive remote monitoring alerts via email when a designated event occurs. Operating without fans, it provides whisper quiet operation and reduced points of failure. The Planar URP652 is ENERGY STAR® Certified.



Specification:

Detail:

Product Name	URP652
Planar Part Number	998-4231-00
Display Resolution	Ultra HD (3840 x 2160)
Screen Size	65in (diagonal)
Aspect Ratio	16:9
Display Technology	Direct-lit LED LCD
Haze	25%
Surface Treatment	AG
Display Active Area	1428.5mm x 803.5mm 56.2" x 31.6"
Viewing Angle (typ)	178°
Backlight	LED
Backlight life (1/2 brightness)	50,000 hrs (typ)
Brightness (typ)	700 nits

Specification:

Detail:

<i>Response Time (typ)</i>	6.5 ms
<i>Frame Rate</i>	60Hz
<i>Contrast Ratio (typ)</i>	10000:1
<i>Contrast Ratio - Dynamic</i>	50000:1
<i>Local Dimming</i>	480 zones
<i>Pixel Pitch</i>	0.372 mm
<i>Color Gamut</i>	90% NTSC
<i>Display Color</i>	>1 billion colors. Full 10 bit data path
<i>External Connections</i>	DisplayPort 2.0 x 2, DisplayPort out x1, HDMI® 2.1 x 2 (HDCP 2.2), USB-C (90W PD) x 1, USB-A x1
<i>Modes</i>	3840x2160 @ 24/25/30/50/60Hz; 1080p @ 24/25/30/50/60Hz; 480p, 576p, 720p @ 50/60 Hz
<i>Display Control</i>	IR, RS-232, LAN, HDMI-CEC, Keypad, Web Browser Interface
<i>Dimensions (W x H x D)</i>	1452.9mm x 828.8mm x 76.5mm 57.2" x 32.6" x 3.0"
<i>Dimensions with Handles (W x H x D)</i>	1452.9mm x 828.8mm x 76.5mm 57.2" x 32.6" x 3.0"
<i>Orientation</i>	Landscape/Portrait
<i>Bezel Width</i>	10mm 0.4"
<i>Display Edge to Active Area</i>	12.2mm 0.5" top, left and right, 13.1mm 0.5" bottom
<i>Weight</i>	31.5 kg 69.4 lbs
<i>Weight (Shipping)</i>	40 kg 88 lbs
<i>Audio Output</i>	Audio Line Out, SPDIF
<i>Speakers</i>	10W x 2 built-in
<i>Enclosure</i>	Aluminum
<i>Mounting</i>	VESA: 400mm x 400mm

Specification:

Detail:

<i>Fanless</i>	Yes
<i>Line Voltage</i>	100-240V; 50/60Hz
<i>Power Consumption (typ)</i>	115W (standby: <0.5W)
<i>AC Output Current (max)</i>	3A
<i>Operating Temperature</i>	0° to +40°C 32° to 104°F up to 5000m
<i>Humidity</i>	20 - 85% RH (non-condensing)
<i>Options / Features</i>	On/Off scheduling, presets, convenient mounting points for third-party accessories
<i>Multi-Source Views</i>	PIP, Dual, Quad
<i>Approvals</i>	FCC Class A, CE, cTUVus, RoHS
<i>ENERGY STAR® Certified</i>	Yes
<i>TAA Compliance</i>	Yes
<i>Security</i>	No WiFi, no Android O/S, signed and encrypted firmware, ability to disable communication interfaces, Secure Shell (SSH) protocol
<i>Warranty</i>	3 years Advance Exchange
<i>Recommended Usage</i>	Up to 24x7
<i>In the Box</i>	URP652 display, power cables - US and EU, HDMI cable, USB-C cable, IR cable, remote control, cable clips and Quick Start Guide
<i>UPC</i>	8 10069 81179 6
<i>HDMI®</i>	Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Planar is a trademark of Planar Systems, Inc. All other trademarks and service marks are property of their holders. Copyright © 2026 Planar Systems, Inc. All rights reserved. This document may not be copied in any form without permission from Planar. Information in this document is subject to change without notice.